

HARKEN®

2.25 in & 3.00 in

The 2.25 in (57 mm) is the original Harken® block. They are compact and lightweight, with fast trim and release under high or low loads. Perfect for dinghies, scows, beachcats and iceboats, as well as small offshore racers and cruisers.

Free-rolling Delrin® ball bearings, sheave and sideplates UV-stabilized with carbon-black additive for maximum protection.

The 3.00 in (76 mm) single block comes in high-load or low-load configurations. High-load blocks feature Torton® bearings and forged stainless steel shackles.

The wire version features Hardkote-anodized, Teflon®-impregnated aluminum sheaves for strength and corrosion resistance.

Use for:
Main and jib sheets
Spinnaker halyards
Control lines

Set screw in three-way head locks shackle in front or side positions, or lets block swivel to keep line from twisting

High-strength stainless steel straps reinforce blocks

Multiple sheave configurations use a bridge coupler to spread the load

Removable becket allow attachment of spliced line



Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Shackle pin Ø		Safe working load		Breaking strength	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
2.25"															
001	Single	2 1/4	57	4 1/4	108	4 1/2	128	3/16	12	3/16	5	500	227	2500	1134
002	Single/becket	2 1/4	57	5	127	5	142	3/16	12	3/16	5	500	227	2500	1134
003	Double	2 1/4	57	4 1/2	114	8 1/2	241	3/16	12	1/4	8	1000	454	3000	1361
004	Double/becket	2 1/4	57	5 1/2	138	9 1/2	269	3/16	12	1/4	8	1000	454	3000	1361
013	Cheek†	2 1/4	57	3 1/4	83	5	142	3/16	12	—	—	500	227	2500	1134
047	Thru-deck*	2 1/4	57	3 1/2	89	5 1/2	158	3/16	12	—	—	500	227	2500	1134
048	Triple	2 1/4	57	5	127	12	340	3/16	12	1/4	8	1200	544	3000	1361
076	Triple/becket	2 1/4	57	5 1/4	146	13 1/2	383	3/16	12	1/4	8	1200	544	3000	1361
153	Light-duty/swivel	2 1/4	57	4 1/2	114	10	284	3/16	12	1/4	8	750	340	2000	907
186	Single/150 Cam-Matic®/becket	2 1/4	57	5	127	10 1/2	298	3/16	12	3/16	5	500	227	2500	1134
206	Upright lead**	2 1/4	57	3 1/4	83	5 1/2	158	3/16	12	—	—	500	227	2500	1134
3.00"															
005	Single	3	76	5	127	7	198	3/16	12	3/16	5	750	340	2500	1134
011	Heavy-duty single	3	76	5 1/4	133	8	227	3/16	12	1/4	8	750	340	3000	1361
012	Heavy-duty single/becket	3	76	6 1/4	159	8 1/2	241	3/16	12	1/4	8	750	340	3000	1361
014	Cheek†	3	76	4	102	6	170	3/16	12	—	—	750	340	2500	1134
202	Wire single	3	76	5 1/4	133	9 1/2	269	3/16	12	1/4	8	850	386	3000	1361

†Includes fasteners & mounting pad *#6 (4 mm) RH fasteners **#10 (5 mm) RH fasteners