

Bullet

HARKEN®

Low-friction Bullet blocks lead control lines aft. They are compact and lightweight, with fast trim and release under high or low loads. A range of styles lets these blocks adapt to almost all control line applications.

Free-rolling Delrin® ball bearings, sheave and sideplates UV-stabilized with carbon-black additive for maximum protection.

Wire Bullet blocks use roller bearings to carry higher loads and feature Hardkote-anodized Teflon® impregnated aluminum sheaves for strength and corrosion resistance. Mast exit blocks with cams used for halyard controls and under boom mainsheets.



Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Shackle pin Ø		Safe working load		Breaking strength	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
Bullet															
082	Single	1 1/2	29	2	51	1	28	1/8	8	—	—	300	136	2000	907
083	Single/becket	1 1/2	29	2 1/4	70	1.25	35	1/8	8	—	—	300	136	2000	907
098	Wire single	1 1/2	29	2	51	1	28	1/8	8	—	—	500	227	2000	907
099	Wire single/becket	1 1/2	29	2 1/4	70	1.25	35	1/8	8	—	—	500	227	2000	907
166	Single/swivel	1 1/2	29	2 1/4	70	1.5	43	1/8	8	3/8	5	300	136	2000	907
167	Single/swivel/becket	1 1/2	29	3 1/2	89	1.75	50	1/8	8	3/8	5	300	136	2000	907
183	Wire swivel	1 1/2	29	2 1/4	70	1.5	43	1/8	8	3/8	5	500	227	2000	907
291	Pivoting exit/423 Carbo-Cam®	1 1/2	29	2 1/4	70	3.75	106	1/4	6	—	—	150	68	2000	907
299	Pivoting exit/423 Carbo-Cam®/becket*	1 1/2	29	2 1/4	70	4	113	1/4	6	3/8	5	150	68	2000	907

Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Shackle pin Ø		Safe working load		Breaking strength	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
Bullet															
084	Double	1 1/2	29	2 1/4	70	2.5	71	1/8	8	1/8	5	400	181	2000	907
085	Double/becket	1 1/2	29	3 1/2	89	2.75	78	1/8	8	1/8	5	400	181	2000	907
086	Triple	1 1/2	29	3	76	3.75	106	1/8	8	1/8	5	500	227	2000	907
087	Triple/becket	1 1/2	29	3 1/2	95	4.5	128	1/8	8	1/8	5	500	227	2000	907
094	Triple/365 Carbo-Cam®	1 1/2	29	3 1/4	95	7	198	1/8	8	1/8	5	500	227	2000	907
095	Triple/365 Carbo-Cam®/becket	1 1/2	29	4	102	7.25	205	1/8	8	1/8	5	500	227	2000	907
100	Double wire	1 1/2	29	2 1/4	70	2.75	78	1/8	8	1/8	5	750	340	2000	907
197	Exit/150 Cam-Matic® (port/stbd)*	1 1/2	29	3	76	4.5	128	1/8	8	—	—	300	136	2000	907
392	4:1 Downhaul/338 Cam-Matic®*	1 1/2	29	8	203	11	313	1/4	6	—	—	400	181	2000	907

W.L. 0-11-14