

Ball Bearing Cam Cleats



Part No.	Description	Height		Length		Width		Weight		Line Ø min - max		Fastener spacing		Safe working load		Breaking strength		Pawls
		in	mm	in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg	
150	Cam-Matic®	1 1/8	30	2 1/8	65	1 1/4	32	2.50	71	1/4 - 1/2	3 - 12	1 1/2	38	300	136	750	340	Aluminum
280	Offshore Cam-Matic®	1 1/4	32	3 1/4	85	1 1/2	38	5.25	148	1/4 - 1/2	6 - 18	2 1/8	52	500	227	1000	454	Aluminum
338	Micro Cam-Matic®	1/4	20	1 1/4	48	1/2	24	.81	23	1/4 - 1/4	3 - 6	1 1/8	27	200	91	400	181	Aluminum
365	Carbo-Cam®	1 1/2	28	2 1/8	65	1 1/4	32	1.44	42	1/4 - 1/4	3 - 10	1 1/2	38	200	91	500	227	Plastic carbon-matrix
412	Double Cam-Matic®	2 1/8	53	3 1/2	81	1 1/4	32	4.50	126	1/4 - 1/4	8 - 10	2 1/8	62	500	227	750	340	Aluminum
423	Micro Carbo-Cam®	1/8	20	1 1/4	48	1/2	24	.56	16	1/8 - 1/4	3 - 6	1 1/8	27	150	68	300	136	Plastic carbon-matrix

*#10 (5 mm) RH fasteners **#8 (4 mm) RH fasteners ***1/4" (6 mm) RH fasteners ****#10 (5 mm) TH fasteners

Cam Kits



Micro Kits

Part No.	Description	Cam	Wedge	Fairlead	Weight	
					oz	g
358	Carbo-Cam®/fairlead	423	—	329	1.13	32
389	Cam-Matic®/fairlead	338	—	329	1.38	39
390	Cam-Matic®/wire fairlead	338	—	284	1.00	28
427	Carbo-Cam®/wire fairlead	423	—	284	.75	22
456	Carbo-Cam®/X-Treme Angle Fairlead	423	—	372	1.00	28
457	Cam-Matic®/X-Treme Angle Fairlead	338	—	372	1.00	28

Standard Kits

Part No.	Description	Cam	Wedge	Fairlead	Weight	
					oz	g
326	Carbo-Cam®/wire fairlead	365	—	298	2.00	54
327	Cam-Matic®/wire fairlead	150	—	298	3.00	85
356	Cam-Matic®/fairlead	150	—	328	4.00	114
357	Carbo-Cam®/fairlead	365	—	328	3.00	80
458	Carbo-Cam®/X-Treme Angle Fairlead	365	—	380	2.00	54
459	Cam-Matic®/X-Treme Angle Fairlead	150	—	375	2.06	58