Micro

HARKEN®

Low-friction Micro blocks are compact and lightweight, with fast trim and release under high or low loads. Ideal for sailboards, smaller dinghies, and for lightly loaded control lines on boats of all sizes.

Free-rolling Delrin® ball bearings, sheave and sideplates UV-stabilized, with carbon-black additive for maximum protection. Stainless steel sideplates for strength.

Sheaves see page 103.

Part No.	Description	Sheave Ø in	Sheave Ø mm	Length in	Length mm	Weight oz	Weight g	Max line Ø in	Max line Ø mm	Shackle pin Ø in	Shackle pin Ø mm	Safe working load lb	Safe working load kg	Breaking strength lb	Breaking strength kg
224	Single	7/8	22	1 1/2	38	1/2	14	1/4	6	—	—	200	91	1200	544
225	Single/becket	7/8	22	2	51	3/4	21	1/4	6	—	—	200	91	1200	544
226	Double	7/8	22	2	51	1 1/2	43	1/4	6	—	—	350	159	1200	544
227	Double/becket	7/8	22	2 1/2	64	1 1/2	43	1/4	6	—	—	350	159	1200	544
228	Triple	7/8	22	2	51	2	57	1/4	6	—	—	500	227	1200	544
229	Triple/becket	7/8	22	2 1/2	64	2 1/4	64	1/4	6	—	—	500	227	1200	544
230	Triple/423 Carbo-Cam®	7/8	22	2	51	3 1/2	99	1/4	6	—	—	500	227	1200	544
231	Triple/423 Carbo-Cam®/becket	7/8	22	2 1/2	64	3 1/2	99	1/4	6	—	—	500	227	1200	544
232	Traveler	7/8	22	2 3/4	71	1 1/4	35	1/4	6	—	—	200	91	1200	544
233	Cheek***	7/8	22	2 1/16	64	1/4	21	1/4	6	—	—	200	91	1200	544
234	Single/shackle	7/8	22	2 1/4	57	1/4	21	1/4	6	3/16	5	200	91	1200	544
235	Single/shackle/becket	7/8	22	2 3/4	71	1	28	1/4	6	3/16	5	200	91	1200	544
242	Thru-deck***	7/8	22	2 5/8	67	1	28	1/4	6	—	—	200	91	1200	544
243	Upright***	7/8	22	1 1/2	38	1	28	1/4	6	—	—	200	91	1200	544
244	Fiddle/V-jam*	7/8	22	3 1/2	89	2	57	1/4	6	3/16	5	350	159	1200	544
245	Fiddle/V-jam/becket**	7/8	22	4	102	2	57	1/4	6	3/16	5	350	159	1200	544
292	Single/swivel	7/8	22	2 5/8	60	1	28	1/4	6	5/32	4	200	91	1200	544
377	Forkhead	7/8	22	1 21/32	42	9/16	16	1/4	6	—	—	200	91	1200	544
443	Block/eyestrap assembly‡	7/8	22	1 1/4	45	9/16	16	1/4	6	—	—	200	91	1000	454

*Use w/225 or 235 **Use w/226 ***#10 (5 mm) RH fasteners ‡#8 (4 mm) RH fasteners