

Midrange Hexaratchets®

Midrange Hexaratchets® grip loaded sheets, yet allow line to be eased with complete control. Free-rolling Delrin® ball bearings, sheave and sideplates UV-stabilized with carbon-black additive for maximum protection. Fast trim and release under high or low loads.

Use for:
Mainsheets
Tackles

HARKEN®

Cam arms adjust to change line angle into cam

Cam reverses for up or down engagement/disengagement

Ratchet switches on or off under load

Set screw in three-way head locks shackle in front or side positions, or swivels freely to keep line from twisting

Eight-sided sheave for 8:1 holding power with 180° wrap



1549



1550



1571



1555



1556



1565



1566

Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Shackle pin Ø		Safe working load		Breaking strength		Turns
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg	
1549	Single	3	76	6 ¹ / ₈	156	14	397	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	1800	816	5000	2268	Clockwise
1550	Single/becket	3	76	7 ¹ / ₈	184	15	425	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	1800	816	5000	2268	Clockwise
1555	Triple/280 Cam-Matic®	3	76	7 ³ / ₄	197	49	1389	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	3800	1724	8500	3856	Clockwise
1556	Triple/280 Cam-Matic®/becket	3	76	8 ³ / ₄	222	51	1446	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	3800	1724	8500	3856	Clockwise
1571	Single	3	76	6 ¹ / ₈	156	14	397	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	1800	816	5000	2268	Counterclockwise
1565	Fiddle/280 Cam-Matic®	3/2	76/51	8 ¹ / ₂	216	26 ¹ / ₂	751	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	1800	816	5000	2268	Clockwise
1566	Fiddle/280 Cam-Matic®/becket	3/2	76/51	9 ¹ / ₂	241	27 ¹ / ₂	780	9 ¹ / ₁₆	14	5 ⁵ / ₁₆	8	1800	816	5000	2268	Clockwise